

MULTI CVTF

**Continuously Variable Transmission (CVT) Fluid fitted with chain or belt
Technosynthese®**

TYPE OF USE

High performance Technosynthese® fluid specially engineered for Continuously Variable Transmission (CVT) gearbox type. Suitable for use in a wide range of vehicles fitted with CVT gearboxes using either chain/pulleys or belt/pulleys design. Especially suitable for vehicles from American car makers GM, FORD, CHRYSLER,..., Asian car makers HONDA, HYUNDAI, KIA, LEXUS, INFINITI, MITSUBISHI, NISSAN, SUBARU, TOYOTA,... or European car makers AUDI, BMW, CITROËN, MERCEDES, PEUGEOT, RENAULT, ...

Attention, not recommended for CVT unit fitting hybrid vehicles. Before use always refer to the owner manual or handbook of the vehicle.

PERFORMANCES

MOTUL MULTI CVTF is a high tech multi vehicles CVT fluid suitable for a wide range of CVT-equipped passenger cars, including belt-CVT and chain-CVT design.

Thanks to its exclusive and dedicated formula, MULTI CVTF:

- Allows fuel economy for cars fitted with CVT automatic gearboxes by providing optimum metal-to-metal friction.
- Provides high anti-shudder performance to avoid engine vibrations for increased comfort.
- Protects gears that are more and more numerous, compact and heavily loaded.
- Gives superior automatic transmission response through smooth shift feel and reduced shift time lag.
- Improves CVT reaction at cold temperature.
- Extends life time duration due to high shear stability at hot temperature and high oxidation resistance.
- Increases wear protection of belt, chain and pulleys.
- Anti-corrosion, anti-foam.

RECOMMENDATIONS

Can be mixed only with similar lubricants.

Oil change: according to manufacturer's recommendations and adapt according to your own use.

Not recommended for CVT unit fitting hybrid vehicles.

Before use always refer to the owner manual or handbook of the vehicle.



MULTI CVTF

Continuously Variable Transmission (CVT) Fluid fitted with chain or belt
Technosynthese®

PROPERTIES

Color	Visual	Blue
Density at 20°C (68°F)	ASTM D1298	0.852
Viscosity at 40°C (104°F)	ASTM D445	34.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	7.2 mm ² /s
Viscosity Index	ASTM D2270	180.0
Flash point	ASTM D92	210.0 °C / 410.0 °F

**Continuously Variable Transmission (CVT) Fluid fitted with chain or belt
Technosynthese®**

OE PERFORMANCES	
AUDI	G 052 180, G 052 516, TL 52 116, Multitronic, TL 52 180, TL 52 516
BMW	83 22 0 136 376, 83 22 0 429 154, EZL 799, EZL 799 A
CHERY	CVT
CHRYSLER	NS-2, CVTF+4
CITROËN	9735 EF, Elfmatic CVT, Elfmatic CVT MV
DAIHATSU	CVTF 3320, AMMIX CVTF DFE, AMMIX CVT Fluid DC, AMMIX CVT Fluid DFE, CVT Fluid DFC, Fluid TC
DODGE	05191184AA, CVTF+4, NS-2
DS (CAPSA)	9735 EF, Elfmatic CVT, Elfmatic CVT MV
FIAT	Tutela Car CVT N.G
FORD	CVT23, CVT30, MERCON C, WSS-M2C928-A, WSS-M2C933-A, XT-7QCFT
GENERAL MOTORS	DEX-CVT, 1940713, 1940714
HONDA	0826099905HE, 087009006, 08200-9006, 08200-HCF-2, HMMF (Honda Multi Matic Fluid) for CVT models only, without wet starting clutch, CVT-F, Genuine CVT Fluid, HCF-2, Z-1 (CVT models only, without starting clutch, not for Honda Jazz & Fit MY 2001-2007)
HYUNDAI	Genuine CVTF, CVT-1, SP III (CVT models only), SP-CVT 1
INFINITI	NS-1, NS-2, NS-3
JEEP	05191184AA, CVTF+4, NS-2, VTF
KIA	CVT-1, SP III (CVT models only), SP-CVT 1
LEXUS	CVTF 3320, CVT FE, Fluid FE, Fluid TC
LIFAN	CVT
MAZDA	CVTF 3320, JWS 3320
MERCEDES-BENZ	A 001 989 46 03, MB 236.20
MG	EM-CVTF
MINI	83 22 0 136 376, EZL 799, 83 22 0 429 154, COOPER EZL 799 A, ZF CVT V1
MINI	83 22 0 136 376, EZL 799, 83 22 0 429 154, COOPER EZL 799 A, ZF CVT V1
MINI	83 22 0 136 376, EZL 799, 83 22 0 429 154, COOPER EZL 799 A, ZF CVT V1
MITSUBISHI	Dia Queen CVTF-J4, CVTF ECO J4, Dia Queen CVTF-J1 (MMC Diaqueen CVT Fluid J1), Dia Queen CVTF-J4+ (MMC Diaqueen CVT Fluid J4 and J4+), SP III (CVT models only), MZ313973
NISSAN	999MP-NS200P, KTF-1, N-CVT, NS-2V, NS-1, NS-2, NS-3
PEUGEOT	9735 EF, Elfmatic CVT, Elfmatic CVT MV
RENAULT	Elfmatic CVT, Elfmatic CVT MV, CVT CK/SK/FK
ROVER	EM-CVTF, Unipart Transmatic ATF
SATURN	22688912, DEX-CVT
SEAT	G 052 180, G 052 516
SUBARU	CVT TR580, CVT TR690, High Torque CVT, iCVTF, K0425Y0710, K0425Y0711, Lineartronic CVTF, Lineartronic II, NS-2, CV30, CVT III Fluid, ECVT, i-CVTF FG, K0421Y0700, Lineartronic chain CVT 3 Fluid, Lineartronic

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

**Continuously Variable Transmission (CVT) Fluid fitted with chain or belt
Technosynthese®**

	chain CVT and CVT II Fluid, Lineartronic High Torque (HT) CVT Fluid
SUZUKI	CVTF 3320, CVT Green 1, CVT Green 2, NS-2, CVTF 4401, CVTF TC, CVT Green 1V
TOYOTA	CVTF 3320, TC, CVTF FE
VOLVO	CVTF 4959
VW	G 052 516, G 052 180
ZOTYE	RDCF01, RDCF02, CVTs
PRODUCTS	
ELF	matic CVT, matic CVT MV
ESSO	EZL 799, FN1975
FUJIIYUKO	i-CVTF FG
IDEMITSU	CVTF-EX1
MOBIL	CVTF 3320
MOPAR PARTS	CVTF+4, CVTplus4
PSA Groupe	9735 EF, Elfmatic CVT, Elfmatic CVT MV
PUNCH	CVTF-EX1
SHELL	Green 1V